

WSM-03 VERTICAL DRYER

- More Efficient than Drying Shakers
- 25 - 40 Tons per hour processing rate
- Decreases waste volumes
- High recovery rate of valuable OBM
- Explosion proof electronics
- Used on over 500 wells since 2016
- Average of 700 bbls returned per well
- Reduce haul off and disposal costs
- Used on wellbores 6"-20" diameters
- Varying screen sizes available

One of the main drivers in our industry is the minimization of the environmental impact of the drilling operation. Terra Oilfield Solutions continues to be very active in working toward this goal.

Dryers have proven to be the preferred technology for drilling non-aqueous discards throughout the international E&P industry. The WSM-03 is specifically designed for limited space applications while delivering drier cuttings and lower volumes of waste.

An added benefit of using a vertical dryer is the ability to return valuable drilling fluid to the active system.

Dimensions (L x H x W)	87.5" x 47.5" x 63.3"
Footprint	38.5 ft ²
Dry Transit Weight	4,200 Lbs
Electrical Specifications	460V, 3Ph, 60Hz, 30HP Drive Motor .75HP Oil Pump Motor Explosion Proof Z1, Div 1
Performance	322 G-Force @ 900 RPM 25-40 TPH of Wet Cuttings Average OCC < 4% wt

